

GUARDIAN



TQ-GUARDIAN-UHF UHF Public Safety BDA UL2524 Listed



FEATURES

- Improves coverage for Public Safety UHF Network Frequencies:
UL:450-512 &DL:450-512MHz
- 90 dB, 2.5-Watt system and 5 W system
- FCC Class A and Class B options available
- Meets the code for NFPA 72/1221 and IFC 510
- UL 2524 Certified and Labeled
- Ethernet port with built-in TowerIQ Sentry remote monitoring web server for browser-based configuration and monitoring
- Integrated dry contact 9-pin alarming
- Automatic gain control (AGC) and Oscillation Detection with automatic remediation
- 24VDC Operation
- Independently adjustable frequency attenuation for uplink and downlink (Reduce gain in -1 dB increments)

Technical Specifications

Certifications	FCC: ID 2AXVJGUARD-UHFA FCC: ID 2AXVJGUARD-UHFB Part 90 UL: 2524
Dimensions	21.2 x 17.2 x 8.0 in
Enclosure Cooling	Convection
Environmental Class	Type 4
Operating Humidity	95%
Operating Temperature	-4 to +122°F (-20 to +50°C)
Power Consumption	90W
Power Supply	DC: 24-30 V
RF Connections	N Female
Weight	45.9 lbs (53 lbs shipped)

Guardian UHF Electrical Specifications

Electrical		
Frequency Range, Uplink	450-512Mhz	
Frequency Range, Downlink	450-512Mhz	
Total Maximum Output Power, Uplink	27dBm	
Total Maximum Output Power, Downlink	34/37dBm	
Maximum System Gain	90dB for Downlink; 85dB for Uplink	
Gain Adjustment Range (1 dB step)	0-30 dB	
AGC Dynamic Range	>60 dB	
Sub-Channel Gain Adjustment Range	30dB	
Pass Band Ripple, p-p	≤10 dB	
Noise Figure @ Max Gain	≤7 dB	
Squelch Adjustment Range	-80 to -90dBm	
Intermodulation	≤-13 dBm	
Impedance	50 Ω	
AC Power Input	100-240 VAC, 50/60 Hz, 2.0 A	
DC Input Range	24 - 30 VDC	
Power Consumption	90W	
Sub-Channel Bandwidth	Class A	12.5/25/75KHz
	Class B	0.7/2/3.5/5/24MHz
Number of Sub-Channel	Class A	32
	Class B	5
System Group Delay (@25KHz BW)	Class A	≤60μsec @ 12.5KHz;
		≤36μsec @ 25KHz;
	Class B	≤15μsec @ 75KHz
Out-of-Band Suppression	Class A	≥60dB@ filter band edge +30 kHz;
		≥60dB@ filter band edge +50 kHz;
	Class B	≥60dB@ filter band edge +210 kHz;
		≥60dB@ filter band edge +1 MHz;
Absolute Maximum RF Input Power	Uplink	-10dBm
	Downlink	0dBm

WARNING

THIS IS NOT A CONSUMER DEVICE. IT IS DESIGNED FOR INSTALLATION BY FCC LICENSEES AND QUALIFIED INSTALLERS. USERS MUST HAVE AN FCC LICENSE OR THE EXPRESS CONSENT OF AN FCC LICENSEE TO OPERATE THIS DEVICE.

UNAUTHORIZED USE MAY RESULT IN SIGNIFICANT FORFEITURE PENALTIES, INCLUDING PENALTIES IN EXCESS OF \$100,000 FOR EACH CONTINUING VIOLATION.

Part 90 Signal Boosters. THIS IS A 90.219 CLASS B DEVICE.